


**OUTLINE NOTES**

- 1) GENERAL ENCLOSURE CONSTRUCTION:
  - A) FREESTANDING ENCLOSURE NEMA 3R
  - B) FABRICATED FROM 14 GA. STEEL
  - C) PAINTED ANSI-61 LIGHT GRAY
  - D) HINGED FRONT DOOR
  - E) PADLOCKABLE
  - F) REMOVABLE REAR & BOTTOM COVERS
  - G) FRONT & REAR ACCESS REQUIRED
  - H) ALL DIMENSIONS EXPRESSED IN INCHES
  - I) GASKETED DOOR & COVERS
  - J) SYSTEM MUST HAVE ALL DOORS & COVERS INSTALLED FOR PROPER OPERATION
- 2) LUGS:
  - (4) #2-600MCM PER PHASE & NEUTRAL
  - (4) #6-350MCM GROUND
- 3) ROOF WITH OVERHANG

|  |             |               |     |           |
|--|-------------|---------------|-----|-----------|
| REV  | DESCRIPTION | BY            | APV | DATE      |
| -  | -           | -             | -   | -         |
| -  | -           | -             | -   | -         |
| -  | -           | -             | -   | -         |
|  <b>LAKE SHORE ELECTRIC Corp</b><br>BEDFORD, OHIO U.S.A.<br>ICFD3XXXXCPSX MP7650 24VDC<br>277/480VAC 3P 3Ø 4W XXXXA   |             |               |     |           |
| SCALE: 1=12 DRN: --- /--- /--- CHK: --- /--- /--- APV: --- /--- /---   |             |               |     |           |
| <small>THIS DOCUMENT IS THE PROPERTY OF Lake Shore Electric Corporation. UNDER COPYRIGHT LAW, DISTRIBUTION AND REPRODUCTION OF THIS DOCUMENT IN WHOLE OR IN PART, IS PROHIBITED WITHOUT PRIOR WRITTEN PERMISSION FROM Lake Shore Electric Corporation.</small> |             |               |     |           |
| PROJ: -  |             |               |     |           |
| CUSTOMER: -  |             | DWG NUMBER: - |     | -         |
| -  |             | QUOTE/JOB#: - |     | PG 1 OF 1 |