



OUTLINE NOTES

- 1) GENERAL ENCLOSURE CONSTRUCTION:
 - A) FREESTANDING ENCLOSURE NEMA 12
 - B) FABRICATED FROM 14 GA. STEEL
 - C) PAINTED ANSI-61 LIGHT GRAY
 - D) HINGED FRONT DOOR
 - E) PADLOCKABLE
 - F) REMOVABLE REAR & BOTTOM COVERS
 - G) FRONT & REAR ACCESS REQUIRED
 - H) ALL DIMENSIONS EXPRESSED IN INCHES
 - I) GASKETED DOOR & COVERS
 - J) SYSTEM MUST HAVE ALL DOORS & COVERS INSTALLED FOR PROPER OPERATION
- 2) LUGS:
 - (10) #2-600MCM PER PHASE & NEUTRAL
 - (10) #6-350MCM GROUND

-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
REV	DESCRIPTION	BY	APV	DATE
LAKE SHORE ELECTRIC Corp BEDFORD, OHIO U.S.A.				
ICDA33000XXXX MP7650 24VDC 277/480VAC 3P 3Ø 4W 3200A				
SCALE: 1=12 DRN: --- /--- /--- CHK: --- /--- /--- APV: --- /--- /---				
<small>THIS DOCUMENT IS THE PROPERTY OF Lake Shore Electric Corporation. UNDER COPYRIGHT LAW, DISTRIBUTION AND REPRODUCTION OF THIS DOCUMENT IN WHOLE OR IN PART, IS PROHIBITED WITHOUT PRIOR WRITTEN PERMISSION FROM Lake Shore Electric Corporation.</small>				
PROJ:	-			
CUSTOMER:	-	DWG NUMBER	-	-
-	-	QUOTE/JOB#:	-	PG 1 OF 1